



L-PLAST 250 BEL-R-90 DM

Safety luminaire in compliance with EN 60598-1/2-22 and EN 1838.

Slim, attractive housing made of polycarbonate with clear hood for ceiling mounting. Screwless, easy-to-use locking mechanism.

For ceiling mounting in longitudinal direction with optics for escape route illumination. Also available as recessed ceiling version with optional recessed ceiling frame.



Technical specifications

Luminaire type	Luminaires for central battery systems	Self contained luminaires
Illuminant	2 W LED-bar	2 W LED-bar
Connecting terminals	2 x 2.5 mm ² for double assignment	
Colour	white	
Material	Polycarbonate (light cover clear)	
Mounting type	Ceiling mounting	
Additional mounting types*	Recessed mounting, Ceiling mounting (wire suspension)	
Dimensions (W x H x D)	DM 239 x 62 x 59 mm	
Protection class	IP54	
Safety class	II	
IK Safety class	IK03	
Light current (mains)	240 lm	240 lm
Light current (emergency)		
Battery duration 1h	–	240 lm
Battery duration 3h	–	105 lm
Luminous flux		
Emergency (DC) / mains		
Battery duration 1h	–	100% / 100%
Battery duration 3h	–	45% / 100%
Power consumption	5.5 VA	5.5 VA
Battery current input	14 mA	–
Battery duration	–	1h / 3h
Battery operation		
Voltage supply	230V 50/60Hz; 220V DC +25/-20%	230V 50/60Hz
NiMH-battery		
Battery duration 1h	–	4,8V 0,8Ah
Battery duration 3h	–	4,8V 0,8Ah
Temperature range	-10°C to +40°C	–
Non-maintained mode	–	0°C to +35°C
Maintained mode	–	-5°C to +30°C
optional		
Multi-switch and monitoring module	ELC MSÜ3 SET009 SET010	–
Self monitoring	–	SELF CHECK
Central monitoring	–	SAFELOG Line
Wireless monitoring	–	SAFELOG Wireless

* Optional accessory required

Accessories


Wire guard

Recessed ceiling frame - clampable



Chain assembly set

Cable assembly set

Ceiling mounting



Lighting data and tables of luminaire distances (E = 1,25 lx)




Ceiling mounting

Mounting direction

Luminaires for central battery systems escape route optics

Distance table for plane emergency routes / distance data in meters




Luminous flux emergency / mains: 240lm

h	2.50	3.00	3.50	4.00	4.50	5.00	5.50
a	18.10	19.80	20.40	20.60	20.40	19.20	17.90
b	7.20	7.40	6.90	6.20	5.80	5.20	4.50
c	-	-	-	-	-	-	-
d	-	-	-	-	-	-	-

Self contained luminaires escape route optics

Distance table for plane emergency routes / distance data in meters




Luminous flux emergency / mains: 240lm/240lm – Battery duration: 1h

h	2.50	3.00	3.50	4.00	4.50	5.00	5.50
a	18.10	19.80	20.40	20.60	20.40	19.20	17.90
b	7.20	7.40	6.90	6.20	5.80	5.20	4.50
c	-	-	-	-	-	-	-
d	-	-	-	-	-	-	-

Self contained luminaires escape route optics

Distance table for plane emergency routes / distance data in meters



Luminous flux emergency / mains: 105lm/240lm – Battery duration: 3h

h	2.50	3.00	3.50
a	13.50	13.50	12.10
b	4.30	3.80	3.20
c	-	-	-
d	-	-	-