

40m

2x2W
LED

IP54

KBOX 400

Modern IP54 exit sign luminaire made of white polycarbonate for universal mounting. Easy, tool-free installation due to click system.

The luminaire can be used for one-sided wall mounting and two-sided ceiling mounting or for wall bracket mounting.

Wall mounted installation with an enclosed fixed rear wall. Ceiling and wall bracket mounting with click adapter which is also enclosed.

In addition, the luminaire is equipped with light emission windows facing downwards.

The luminaire is equipped with a 2x2 watt LED bar.



Technical specifications

Visibility distance	40 m
Connecting terminals	2 x 2,5 mm ² for double assignment
Casing/colour	Polycarbonate/white
Type of assembly	Ceiling mounting, wall mounting, wall bracket mounting
Dimensions (WxHxD)	
Ceiling	420 x 241 x 80 mm
Wall	420 x 220 x 82 mm
Wall bracket	441 x 220 x 80 mm
Protection class	IP54
Safety class	II

	■ Luminaires for central battery systems	■ Self contained luminaires
Illuminant	2 x 2 W LED-bar	2 x 2 W LED-bar
Light current mains operation	460lm	460lm
Luminous flux		
Emergency (DC)/mains 1h/3h	-	40% / 100%
Emergency (DC)/mains 8h	-	25% / 100%
Power consumption	8,9 VA	9,6 VA
Battery current input	25mA	-
Rated operating time		
Battery operation	-	1h/3h/8h
Voltage supply	230V 50/60Hz / 220V DC +25/-20%	230V 50/60Hz
NiMh-Akku	-	4,8V 2,0Ah
Temperature range	-10°C to +40°C	-
non-maintained mode	-	-0°C to +35°C
maintained mode	-	-5°C to +30°C
optional:		
Multi-switch and monitoring module	ELC, MSÜ3, SET009, SET010, DALI	-
Self monitoring	-	SELF CHECK
Central monitoring	-	SAFELOG Line SAFELOG Wireless

Accessories

Accessories	Pictogram-set*
Chain assembly set	Exit pictogram FR
Cable assembly set	Exit pictogram FL
Central pendulum	Exit pictogram FU
	Blind pane

* Pictogram-set included in the delivery.
Other pictograms available on request.

