









ALULINE A200 UM

Elegant and modern design, made of aluminum in white or black, special colors possible.

By simply remounting the container, the luminaire can be used universally for ceiling and wall mounting. A 90 degree parallel wall mounting is also possible, a corresponding pictogram set is optionally available.

With the two accessory sets, central pendulum and wire mounting, the luminaire is very changeable and versatile.

The 10 mm light-deflecting pane is illuminated with a 1 or 2 watt LED-bar. A pictogram set with arrow left / right / down / blind is already enclosed.

Technical specifications

Visibility distance 23 m

Connecting terminals 2 x 2,5 mm² for double assignment Aluminum die-cast / white or black

Type of assembly Universal mounting

Dimensions (WxHxD)

 Ceiling
 254 x 194 x 83 mm

 Wall
 254 x 164 x 53 mm

Protection class IP40 Safety class II


	Luminaires for central battery systems		Self contained luminaires	
Illuminant	1 W	2 W	1 W	2 W
	LED-bar	LED-bar	LED-bar	LED-bar
Light current mains operation	130lm	260lm	130lm	260lm
Luminous flux				
Emergency (DC)/mains 1h/3h/8h	-		15-50%/100%	
Power consumption	4,5 VA	5,5 VA	4,5 VA	5,5 VA
Battery current input	11mA	14mA		-
Rated operating time				
Battery operation	-		1h/3h/8h	
Voltage supply	230V 50/60Hz / 220V DC +25/-20%		230V 50/60Hz	
NiMh-Akku	-		4,8V 0,8Ah	
Temperature range	-10°C to +40°C			-
Non-maintained mode	-		-0°C to +35°C	
Maintained mode	-		-5°C to +30°C	
optional:				
Multi-switch and monitoring module	ELC, MSÜ3, SET009, SET010		-	
Self monitoring	-		SELF CHECK	
Central monitoring	-		SAFELOG Line SAFELOG Wireless	


Accessories	Pictogram-set*
Central pendulum set	Exit pictogram FR
Cable assembly set	Exit pictogram FL
Universal cover plate for ceiling cutouts	Exit pictogram FU
Back box with lateral cable entry	Blind pane

Various single pictograms as well as sets
















^{*} Pictogram-set included in the delivery. Other pictograms available on request.