



# ALULINE A300 UM

Elegant and modern design, made of aluminum in white or black, special colors possible.

By simply remounting the container, the luminaire can be used universally for ceiling and wall mounting. A 90 degree parallel wall mounting is also possible, a corresponding pictogram set is optionally available.

With the two accessory sets, central pendulum and wire mounting, the luminaire is very changeable and versatile.

The 10mm light-deflecting pane is illuminated with a 1,5 or 3 watt LED-bar. A pictogram set with arrow left / right / down / blind is already enclosed.

## Technical specifications

Visibility distance	30m
Connecting terminals	2 x 2,5 mm <sup>2</sup> for double assignment
Casing/colour	Aluminum die-cast / white or black
Type of assembly	Universal mounting
Dimensions (WxHxD)	
Ceiling	329 x 233 x 83 mm
Wall	329 x 203 x 53 mm
Protection class	IP40
Safety class	II

Illuminant	■ Luminaires for central battery systems		■ Self contained luminaires	
	1,5W LED-bar	3W LED-bar	1,5W LED-bar	3W LED-bar
Light current mains operation	190lm	350lm	190lm	350lm
Luminous flux				
Emergency (DC)/mains 1h/3h/8h	-		15-50%/100%	
Power consumption	5VA	6VA	5VA	6VA
Battery current input	12mA	19mA	-	
Rated operating time				
Battery operation	-		1h/3h/8h	
Voltage supply	230V 50/60Hz / 220V DC +25/-20%		230V 50/60Hz	
NiMh-Akku	-		4,8V 0,8Ah	
Temperature range	-10°C to +40°C		-	
Non-maintained mode	-		-0°C to +35°C	
Maintained mode	-		-5°C to +30°C	
optional:				
Multi-switch and monitoring module	ELC, MSÜ3, SET009, SET010		-	
Self monitoring	-		SELF CHECK	
Central monitoring	-		SAFELOG Line SAFELOG Wireless	

## Accessories

Accessories	Pictogram-set*
Central pendulum set	Exit pictogram FR
Cable assembly set	Exit pictogram FL
Universal cover plate for ceiling cutouts	Exit pictogram FU
Back box with lateral cable entry	Blind pane

Various single pictograms as well as sets \* Pictogram-set included in the delivery. Other pictograms available on request.

